

470 TURNBULL RELOADING DATA

CASE OVERALL LENGTH: 2.050" • MAXIMUM CARTRIDGE OAL: 2.550"



350 GRAIN BARNES TSX

	VELOCITY (feet per second)					
POWDER	1,875	1,880	1,950			
H322	59 gr.	x	60 gr.			
IMR4198	x	52.5 gr.	53.5 gr.			

400 GRAIN BARNES TSX & 400 GRAIN SPEER

	VELOCITY (feet per second)					
POWDER	1,710	1,730	1,750	1,810	1,840	1,850
AC2015	55 gr.	x	x	56 gr.	x	x
H322	x	56 gr.	x	x	x	57 gr.
IMR4198	x	x	49 gr.	x	50 gr.	x
	Note: reduce above loads 1.5 gr. for 400 BARNES SOLID					

450 GRAIN BARNES BANDED SOLID

	VELOCITY (feet per second)					
POWDER	1,710	1,720	1,730	1,770	1,780	1,790
AC2015	x	x	52.1 gr.	x	x	52.6 gr.
H322	x	51.2 gr.	x	52 gr.	x	x
IMR4198	46 gr.	x	x	x	47 gr.	x

Disclaimer: USE THIS DATA AT YOUR OWN RISK. Turnbull Restoration Co., Inc., its staff, members, and contributors take NO responsibility for any and all injuries including death, losses or damages to person or property (including consequential damages), arising from the use of any of this data, whether or not occasioned by publisher's negligence or based on strict liability or principles of indemnity or contribution. Turnbull Restoration (www.turnbullrestoration.com) or any persons involved with Turnbull Restoration neither assumes nor authorizes any person to assume for it any liability in connection with the use of any product or data. Turnbull Restoration is not responsible for the data presented or its use. In addition we are not responsible for typographical errors or interpretation of this data. *Use Reloading data at your own risk.*

TURNBULL RESTORATION CO., INC.

(585) 657-6338 • INFO@TURNBULLRESTORTION.COM • WWW.TURNBULLRESTORATION.COM

Rev. 012519